

PRIMO A C1 180 NM AT W TM-A0.C1.AT04W

Click on the selected icon to download the file:



No: 1725



No: 6077/2026
Valid until:
19.05.2031



No: B_BK_60112_0427_2024
Valid until:
24.01.2030




No: 1725



No: DC-UAE-0374
Valid until:
19.05.2031



No: 1725





No: V1



No: V1.2



Producer	TM TECHNOLOGIE
Application	escape route lighting
Family	PRIMO A
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	I
Material	steel
Installation method*	surface, ceiling
Luminous flux emergency	444* lm
Light source	LED
Maximum light power	4.5 W
Active power	4.1 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+5 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 3.0-3.2Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	273 mm x 61 mm x 75 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.