
PRIMO A M2 180 NM AT M
TM-A0.M2ATN800M


Click on the selected icon to download the file:

No: 1726 | No: 6077/2026 Valid until: 19.05.2031 | No: B_BK_60112_0427_2024 Valid until: 24.01.2030 | No: 1726 | No: DC-UAE-0374 Valid until: 19.05.2031 | No: 1726 | No: DIT.V1.01 | No: V1.2



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**PRIMO A**
Colour	**mirror**
Colour - RAL	**RAL9003**
Version	**autotest**
Operating mode	**NM**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**I**
Material	**stainless steel**
Installation method*	**surface, ceiling**
Luminous flux emergency	**651 lm**
Light source	**LED**
Maximum light power	**5.1 W**
Active power	**3.6 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Colour temperature	**5700 K**
Minimum temperature	**+5 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 6.4V 4.5-4.8Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **L x W x H** [±2 mm]	**323 mm x 61 mm x 75 mm**





* Some of mounting methods are possible only with additonal accessory dedicated for that product.