

# ONTEC APN 31P M AT B TM-AN.31P.AT03B

Click on the selected icon to download the file:



No: 1525



No: 1525




No: 1525



No: V1.4

Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>ONTEC AP</b>
Colour/Colour - RAL	<b>black , RAL9005</b>
Colour structure	<b>smooth, gloss</b>
Version	<b>autotest</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK06</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>ceiling, surface</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram included	<b>yes</b>
Evacuation sign dimensions	<b>311x158 mm</b>
Pictogram type	<b>foil</b>
Graphic number	<b>K3</b>
Luminous flux	<b>&gt;200 cd/m<sup>2</sup></b>
Visibility	<b>32 m</b>
Colour temperature	<b>5700</b>
Nominal voltage AC	<b>210-250 V</b>
Light source	<b>LED</b>
LED lifetime	<b>50000 h</b>
Battery	<b>LiFePO4/C (LN) 6.4V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>36 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>403 mm x 61 mm x 211 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.