

ONTEC APN 31P M DALI W TM-AN.31P.DA03W

Click on the selected icon to download the file:



No: 1525



No: 88-116197



No: 1525



No: 3673



No: 1525



No: DIT_001




No: V1.4



DiiA Certificate

<https://www.dali-alliance.org/products/3673/led-ew>

Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC AP
Colour/Colour - RAL	white , RAL9003
Version	DALI
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Colour structure	smooth, gloss
Installation method*	ceiling, surface
Adapted to use a pictogram	yes
Luminous flux	>200 cd/m²
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	2.5 W
LED lifetime	50000 h
Colour temperature	5700
Minimum temperature	+10 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
DALI type	A
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	403 mm x 61 mm x 211 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.