

# PRIMO AP 30D 180 M DATA2 B

## TM-AP.30D.BD03B

Click on the selected icon to download the file:



No: 1725



No: 4329/2021  
Valid until:  
19.05.2026



No: B\_BK\_60112\_0427\_2024  
Valid until:  
24.01.2030



No: 1725



No: DC-UAE-0180  
Valid until:  
19.05.2026



No: 1725




No: DIT\_001



No: V1.0



|  |                                      |
|--|--------------------------------------|
| Producer                                   | <b>TM Technologie</b>                |
| Category                                   | <b>emergency luminaires</b>          |
| Application                                | <b>evacuation route direction</b>    |
| Family                                     | <b>PRIMO AP</b>                      |
| Colour/Colour - RAL                        | <b>black , RAL9005</b>               |
| Colour structure                           | <b>painted</b>                       |
| Version                                    | <b>DATA2</b>                         |
| Operating mode                             | <b>M</b>                             |
| Duration time                              | <b>3 h</b>                           |
| Protection degree                          | <b>IP20</b>                          |
| Impact protection degree                   | <b>IK07</b>                          |
| Appliance classes                          | <b>I</b>                             |
| Material                                   | <b>steel</b>                         |
| Installation method*                       | <b>ceiling</b>                       |
| Adapted to use a pictogram                 | <b>yes</b>                           |
| Pictogram included                         | <b>yes</b>                           |
| Pictogram dimensions                       | <b>300x150 mm</b>                    |
| Evacuation sign dimensions                 | <b>300x150 mm</b>                    |
| Pictogram type                             | <b>sticker</b>                       |
| Graphic number                             | <b>K3</b>                            |
| Luminous flux                              | <b>&gt;500 cd/m<sup>2</sup></b>      |
| Visibility                                 | <b>30 m</b>                          |
| Colour temperature                         | <b>5700 K</b>                        |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>2 W</b>                           |
| LED lifetime                               | <b>50000 h</b>                       |
| Minimum temperature                        | <b>+5 °C</b>                         |
| Maximum temperature                        | <b>+40 °C</b>                        |
| Battery                                    | <b>LiFePO4/C (LN) 6.4V 1.5-1.6Ah</b> |
| Warranty (body, electronics, light source) | <b>60 months</b>                     |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>323 mm x 61 mm x 228 mm</b>       |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.