

# PRIMO AP 30D 180 M DATA2 W TM-AP.30D.BD03W

Click on the selected icon to download the file:



No: 1725



No: 4329/2021  
Valid until:  
19.05.2026



No:  
B\_BK\_60112\_0427\_2024  
Valid until:  
24.01.2030



No: 1725



No: DC-UAE-  
0180  
Valid until:  
19.05.2026



No: 1725



No: DIT\_001



No: V1.0



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>PRIMO AP</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Colour structure	<b>painted</b>
Version	<b>DATA2</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK07</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>ceiling</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram included	<b>yes</b>
Pictogram dimensions	<b>300x150 mm</b>
Evacuation sign dimensions	<b>300x150 mm</b>
Pictogram type	<b>sticker</b>
Graphic number	<b>K3</b>
Luminous flux	<b>&gt;500 cd/m<sup>2</sup></b>
Visibility	<b>30 m</b>
Colour temperature	<b>5700 K</b>
Nominal voltage AC	<b>210-250 V</b>
Light source	<b>LED</b>
Maximum light power	<b>2 W</b>
LED lifetime	<b>50000 h</b>
Minimum temperature	<b>+5 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 6.4V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>323 mm x 61 mm x 228 mm</b>

