

PRIMO AP 40D 180 M DATA2 B

TM-AP.40D.BD03B

Click on the selected icon to download the file:



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No:
B_BK_60112_0427_2024
Valid until:
24.01.2030




No: 1725



No: DC-UAE-
0180
Valid until:
19.05.2026



No: 1725




No: DIT_001



No: V1.0



| | |
|--|--------------------------------------|
| Producer | TM Technologie |
| Category | emergency luminaires |
| Application | evacuation route direction |
| Family | PRIMO AP |
| Colour/Colour - RAL | black , RAL9005 |
| Colour structure | painted |
| Version | DATA2 |
| Operating mode | M |
| Duration time | 3 h |
| Protection degree | IP20 |
| Impact protection degree | IK07 |
| Appliance classes | I |
| Material | steel |
| Installation method* | ceiling |
| Adapted to use a pictogram | yes |
| Pictogram included | yes |
| Pictogram dimensions | 400x200 mm |
| Evacuation sign dimensions | 400x200 mm |
| Pictogram type | sticker |
| Graphic number | K3 |
| Luminous flux | >500 cd/m² |
| Visibility | 40 m |
| Colour temperature | 5700 K |
| Nominal voltage AC | 210-250 V |
| Light source | LED |
| Maximum light power | 2 W |
| LED lifetime | 50000 h |
| Minimum temperature | +5 °C |
| Maximum temperature | +40 °C |
| Battery | LiFePO4/C (LN) 6.4V 1.5-1.6Ah |
| Warranty (body, electronics, light source) | 60 months |
| Net dimensions L x W x H [±2 mm] | 423 mm x 61 mm x 261 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.