

ITECH C2 105 M DATA2 B

TM-IT.C2DDM160B

Click on the selected icon to download the file:



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960




No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 0925




No: V1







No: V2.12



Producer	TM TECHNOLOGIE
Application	escape route lighting
Family	ITECH
Colour/Colour - RAL	black , RAL9005
Version	DATA2
Operating mode	M
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	478 lm
Light source	LED
Maximum light power	4.5 W
Active power	6 W
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
Warranty (body, electronics, light source)	60 months
Net dimensions H x Ø [±2 mm]	74 mm x 171 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	8,5	19,5	-	-
3	10	22	-	-
4	12	27,5	-	-
5	13,5	32	-	-
6	15	36	-	-
7	12	39	-	-
8	7	35	-	-
9	5,5	30	-	-
10	5,5	25	-	-

$E_{min} \geq 1 \text{ lx}$