TM TECHNOLOGIE

# ITECH C2 305 M DATA2 B
# TM-IT.C2DDM360B


Click on the selected icon to download the file:


No: 0926 | No: 4570/2022 Valid until: 10.04.2027 | No: 88-137960 | No: B_BK_60112_0422_2024 Valid until: 24.01.2030 | No: 0926 | No: 0926 | No: DIT.V1.01

No: V3.0



| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Application | **escape route lighting** |
| Family | **ITECH** |
| Colour | **black** |
| Colour - RAL | **RAL9005** |
| Version | **DATA2** |
| Operating mode | **M** |
| Duration time | **3 h** |
| Protection degree | **IP65** |
| Impact protection degree | **IK06** |
| Appliance classes | **II** |
| Material | **plastic** |
| Installation method* | **surface, flush-mounted, suspended, ceiling, at an angle** |
| Luminous flux emergency | **478 lm** |
| Light source | **LED** |
| Maximum light power | **4.5 W** |
| Active power | **6 W** |
| LED lifetime | **100000 h** |
| Nominal voltage AC | **210-250 V** |
| Nominal voltage DC | **- V** |
| Colour temperature | **5700 K** |
| Minimum temperature | **+ 0 °C** |
| Maximum temperature | **+40 °C** |
| Battery | **LiFePO4/C (LN) 6.4V 3.0-3.2Ah** |
| Warranty (body, electronics, light source) | **60 months** |
| Net dimensions **H x Ø** [±2 mm] | **74 mm x 171 mm** |



* Some of mounting methods are possible only with additonal accessory dedicated for that product.