

ITECH S1 60 NM ST W

TM-IT.S1STN660W

Click on the selected icon to download the file:



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960



No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 0925



No: V1




No: V2.12




Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ITECH
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	377 lm
Light source	LED
Maximum light power	2 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah

Warranty (body, electronics, light source) **24 months**

Net dimensions **H x Ø [±2 mm]** **74 mm x 171 mm**





2,5		6	14	6	14
3		7	16	7	16
4		8	18	8	18
5		4	18	4	18
6		3	17	3	17
7		4	16	4	16
8		-	-	-	-
9		-	-	-	-
10		-	-	-	-

$E_{min} \geq 0,5 \text{ lx}$