ONTEC C C1 302 M DALI W
TM-OC.C1DAM300W


Click on the selected icon to download the file:

No: 0126 | No: 6232/2026 Valid until: 11.09.2031 | No: B_BK_60112_0424_2024 Valid until: 24.01.2030 | No: 0126 | No: 3327 | No: 0126 | No: DIT.V1.01


No: V3.0



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**escape route lighting**
Family	**ONTEC C**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**DALI**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**II**
Material	**plastic**
Colour structure	**matte , satin, smooth**
Installation method*	**flush-mounted**
Luminous flux emergency	**260 lm**
Nominal voltage AC	**210-250 V**
Light source	**LED**
Maximum light power	**3 W**
Active power	**7 W**
LED lifetime	**50000 h**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **H x Ø** [±2 mm]	**14 mm x 90 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	9	20	-	-
3	10	23	-	-
4	11	27,5	-	-
5	9,5	30	-	-
6	6	30	-	-
7	3,5	25	-	-
8	3,5	20	-	-
9	-	-	-	-
10	-	-	-	-

Emin ≥ 1 lx