

ONTEC C C1 302 M DALI W TM-OC.C1DAM300W

Click on the selected icon to download the file:



No: 0125



No: 4397/2021
Valid until:
11.09.2026



No: B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0125



No: 3327



No: 0125



No: DIT_001



No: V1.14



DiiA Certificate

<https://dali-alliance.org/products/3327/vjp-rs>

Producer

TM Technologie

Category

emergency luminaires

Application

escape route lighting

Family

ONTEC C

Colour/Colour - RAL

white , RAL9003

Version

DALI

Operating mode

M

Duration time

3 h

Protection degree

IP20

Impact protection degree

IK03

Appliance classes

II

Material

plastic

Colour structure

matte , satin, smooth

Installation method*

flush-mounted, ceiling

Luminous flux emergency

260 lm

Nominal voltage AC

210-250 V

Light source

LED

Maximum light power

3 W

LED lifetime

50000 h

Colour temperature

5700 K

Minimum temperature

+10 °C

Maximum temperature

+35 °C

Battery

LiFePO4/C (LN) 6.4V 1.5-1.6Ah

DALI type


A

Warranty (body, electronics, light source)

60 months

Net dimensions **H x Ø** [±2 mm]

14 mm x 90 mm





2,5	9	20	-	-
3	10	23	-	-
4	11	27,5	-	-
5	9,5	30	-	-
6	6	30	-	-
7	3,5	25	-	-
8	3,5	20	-	-
9	-	-	-	-
10	-	-	-	-

$E_{min} \geq 1 \text{ lx}$