

# ONTEC C M1 CB 24/48 W TM-OC.M1CBL000W

Click on the selected icon to download the file:



No: 4525



No:  
B\_BK\_60112\_0424\_2024  
Valid until:  
24.01.2030



No: 4525





No: 4525



No: V1.14



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting</b>
Family	<b>ONTEC C</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>CB 24/48V - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK03</b>
Appliance classes	<b>III</b>
Material	<b>plastic</b>
Installation method*	<b>flush-mounted, ceiling</b>
Luminous flux emergency	<b>338 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>3 W</b>
Active power	<b>4.5 W</b>
Nominal voltage AC	<b>- V</b>
Nominal voltage DC	<b>20-57 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-25 °C</b>
Maximum temperature	<b>+55 °C</b>
Battery	<b>-</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>H x Ø</b> [±2 mm]	<b>14 mm x 90 mm</b>



h	a	b	c	d
2,5	3,5	8	3,5	8
3	4	9	4	9
4	5	11	5	11
5	5,5	13	5,5	13
6	5,5	15	5,5	15
7	6	16,5	6	16,5
8	6	18	6	18
9	5,5	19	5,5	19
10	5	20	5	20

E<sub>min</sub> ≥ 0,5 lx

\* Some of mounting methods are possible only with additional accessory dedicated for that product.