

ONTEC R C1 302 M DALI W TM-OR.C1DAM300W

Click on the selected icon to download the file:



No: 0426



No: 6228/2026
Valid until:
04.09.2031



No: B_BK_60112_0424_2024
Valid until:
24.01.2030




No: 0426



No: 3669



No: 0426




No: V1






No: V3.0



Producer	TM TECHNOLOGIE
Category	emergency luminaires
Application	escape route lighting
Family	ONTEC R
Colour/Colour - RAL	white , RAL9003
Version	DALI
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Colour structure	matte , satin, smooth
Installation method*	surface, flush-mounted, wall, ceiling, at an angle
Luminous flux emergency	246 lm
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	2 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
DALI type	A
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	130 mm x 31 mm x 130 mm





2,5	8,5	19	-	-
3	9,5	22	-	-
4	11	26	-	-
5	12	30	-	-
6	5,5	30	-	-
7	4,5	20	-	-
8	4	18	-	-
9	-	-	-	-
10	-	-	-	-

$E_{min} \geq 1 \text{ lx}$