

ONTEC R C2 105 M DALI W TM-OR.C2DAM100W

Click on the selected icon to download the file:



No: 0426



No: 6228/2026
Valid until:
04.09.2031



No: B_BK_60112_0424_2024
Valid until:
24.01.2030




No: 0426



No: 4907



No: 0426




No: V1




No: V3.0







Producer	TM TECHNOLOGIE
Category	emergency luminaires
Application	escape route lighting
Family	ONTEC R
Colour/Colour - RAL	white , RAL9003
Version	DALI
Operating mode	M
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Colour structure	matte , satin, smooth
Installation method*	surface, flush-mounted, wall, ceiling, at an angle
Luminous flux emergency	541 lm
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	4.5 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
DALI type	A
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	130 mm x 31 mm x 130 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



					
2,5		9,5	20	-	-
3		10,5	23	-	-
4		13	29	-	-
5		15	33	-	-
6		17	38	-	-
7		18	42	-	-
8		18	45	-	-
9		14	45	-	-
10		7	35	-	-

$E_{min} \geq 1 \text{ lx}$