
ONTEC R C2 105 M DALI W
TM-OR.C2DAM100W

Click on the selected icon to download the file:


No: 0426 | No: 6228/2026 Valid until: 04.09.2031 | No: B_BK_60112_0424_2024 Valid until: 24.01.2030 | No: 0426 | No: 4907 | No: 0426 | No: DIT.V1.01 | No: V3.0



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**escape route lighting**
Family	**ONTEC R**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**DALI**
Operating mode	**M**
Duration time	**1 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**II**
Material	**plastic**
Colour structure	**matte , satin, smooth**
Installation method*	**surface, flush-mounted, wall, ceiling, at an angle**
Luminous flux emergency	**541 lm**
Nominal voltage AC	**210-250 V**
Light source	**LED**
Maximum light power	**4.5 W**
Active power	**6.7 W**
LED lifetime	**50000 h**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**130 mm x 31 mm x 130 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	9,5	20	-	-
3	10,5	23	-	-
4	13	29	-	-
5	15	33	-	-
6	17	38	-	-
7	18	42	-	-
8	18	45	-	-
9	14	45	-	-
10	7	35	-	-

Emin ≥ 1 lx