

ONTEC PPN 31P CBA B

TM-PN.31P.CBA1B

Click on the selected icon to download the file:



No: 1525



No: 88-116197



No: 1525



No: 1525



No: V1




No: V1.4



Producer	TM TECHNOLOGIE
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC PP
Colour/Colour - RAL	black , RAL9005
Colour structure	smooth, gloss
Version	CBA - central addressable battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	ceiling, flush-mounted
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	311x158 mm
Evacuation sign dimensions	311x158 mm
Pictogram type	foil
Graphic number	K3
Luminous flux	>200 cd/m²
Visibility	32 m
Colour temperature	5700
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	2.5 W
LED lifetime	50000 h
Minimum temperature	-10 °C
Maximum temperature	+40 °C

Warranty (body, electronics, light source) **60 months**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.