

ONTEC PPN 31P M DATA2 RADIO W TM-PN.31P.DR03W

Click on the selected icon to download the file:



No: 1525



No: 88-116197



No: 1525



No: 1525




No: DIT_001



No: V1.4



| | |
|--|--------------------------------------|
| Producer | TM Technologie |
| Category | emergency luminaires |
| Application | evacuation route direction |
| Family | ONTEC PP |
| Colour/Colour - RAL | white , RAL9003 |
| Colour structure | smooth, gloss |
| Version | DATA2 RADIO |
| Operating mode | M |
| Duration time | 3 h |
| Protection degree | IP20 |
| Impact protection degree | IK06 |
| Appliance classes | II |
| Material | plastic |
| Installation method* | ceiling, flush-mounted |
| Adapted to use a pictogram | yes |
| Pictogram included | yes |
| Pictogram dimensions | 311x158 mm |
| Evacuation sign dimensions | 311x158 mm |
| Pictogram type | foil |
| Graphic number | K3 |
| Luminous flux | >200 cd/m² |
| Visibility | 32 m |
| Colour temperature | 5700 |
| Nominal voltage AC | 210-250 V |
| Light source | LED |
| Maximum light power | 2.5 W |
| LED lifetime | 50000 h |
| Minimum temperature | +10 °C |
| Maximum temperature | +40 °C |
| Battery | LiFePO4/C (LN) 6.4V 1.5-1.6Ah |
| Warranty (body, electronics, light source) | 60 months |
| Net dimensions L x W x H [±2 mm] | 403 mm x 108 mm x 211 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.