

ONTEC PN 302 M DALI W TM-PN.M2.DA03W

Click on the selected icon to download the file:



No: 1525



No: 88-116197




No: 1525



No: 3673



No: 1525



No: DIT_001




No: V1.4



DiiA Certificate

<https://www.dali-alliance.org/products/3673/led-ew>

| | |
|--|--------------------------------------|
| Producer | TM Technologie |
| Category | emergency luminaires |
| Application | anti-panic lighting |
| Family | ONTEC P |
| Colour/Colour - RAL | white , RAL9003 |
| Version | DALI |
| Operating mode | M |
| Duration time | 3 h |
| Protection degree | IP20 |
| Impact protection degree | IK08 |
| Appliance classes | II |
| Material | plastic |
| Colour structure | smooth, gloss |
| Installation method* | flush-mounted, ceiling |
| Luminous flux emergency | 241 lm |
| Nominal voltage AC | 210-250 V |
| Light source | LED |
| Maximum light power | 2.5 W |
| LED lifetime | 50000 h |
| Colour temperature | 5700 |
| Minimum temperature | +10 °C |
| Maximum temperature | +40 °C |
| Battery | LiFePO4/C (LN) 6.4V 1.5-1.6Ah |
| DALI type | A |
| Warranty (body, electronics, light source) | 60 months |



* Some of mounting methods are possible only with additional accessory dedicated for that product.