

INDUST RM 310D CB A

TM-RM.DOCB0310A

Click on the selected icon to download the file:



No: 3025



No: 5047/2023
Valid until:
26.07.2028



No: 3025



No: 3025



No: V1.0



| | |
|--|------------------------------------|
| Producer | TM Technologie |
| Category | emergency luminaires |
| Application | evacuation route direction |
| Family | INDUST RM |
| Colour structure | raw |
| Version | CB - central battery |
| Operating mode | CB |
| Protection degree | IP66, IP69 |
| Impact protection degree | IK08 |
| Appliance classes | I |
| Material | stainless steel |
| Installation method* | surface, wall |
| Adapted to use a pictogram | yes |
| Pictogram dimensions | 353.2x209.2, 353.2x359.2 mm |
| Pictogram type | plexiglass PMMA |
| Luminous flux | >200 cd/m² |
| Visibility | 30 m |
| Colour temperature | 5700 K |
| Nominal voltage AC | 220-240 V |
| Nominal voltage DC | 186-254 V |
| Light source | LED |
| Maximum light power | 1.5 W |
| LED lifetime | 50000 h |
| Minimum temperature | -25 °C |
| Maximum temperature | +45 °C |
| Warranty (body, electronics, light source) | 60 months |
| Net dimensions L x W x H [±2 mm] | 243 mm x 398 mm x 1103 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.