TM TECHNOLOGIE


INDUST RM 300D CB DALI-2 A
TM-RM.D0CD0300A

Click on the selected icon to download the file:

No: 3026 | No: 5047/2023 Valid until: 26.07.2028 | No: 3026 | No: 2016 | No: 3026 | No: V1.0



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**INDUST RM**
Colour	**raw**
Colour structure	**raw**
Version	**CD - CB DALI2**
Operating mode	**CB**
Protection degree	**IP66, IP69**
Impact protection degree	**IK08**
Appliance classes	**I**
Material	**stainless steel**
Installation method*	**surface, wall**
Adapted to use a pictogram	**yes**
Pictogram dimensions	**353, 2x359, 2 mm**
Evacuation sign dimensions	**300x300 mm**
Pictogram type	**plexiglass PMMA**
Luminous flux	**>200 cd/m²**
Visibility	**60 m**
Colour temperature	**5700 K**
Nominal voltage AC	**220-240 V**
Nominal voltage DC	**186-254 V**
Light source	**LED**
Maximum light power	**1.5 W**
Active power	**5.3 W**
LED lifetime	**50000 h**
Minimum temperature	**-25 °C**
Maximum temperature	**+45 °C**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**243 mm x 398 mm x 366 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.