

ONTEC S20 M2X CBM B IP65 TM-S2.MXCBM060B

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-144520
Valid until:
28.02.2027



No: 1625



No: 2291559.01.UAE
Valid until:
28.10.2026



No: 1625




No: V2







No: V3.0



Producer	TM TECHNOLOGIE
Application	anti-panic lighting, evacuation route direction
Family	ONTEC S20
Colour/Colour - RAL	black , RAL9005
Version	CBM - Central addressable modulation battery
Operating mode	CB
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux	>2 cd/m²
Luminous flux emergency	154(L);309(H) lm
Light source	LED
Maximum light power	2.5 W
Active power	4.4 W
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
LED lifetime	100000(L);50000(H) h
Colour temperature	5700 K
Minimum temperature	-15 °C
Maximum temperature	+55 °C
Battery	-
Power Factor Correction	0,76
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	227 mm x 40 mm x 120 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	8	3,5	8
3	3,5	9	3,5	9
4	4,5	11	4,5	11
5	5	12,5	5	12,5
6	5	14,5	5	14,5
7	5	16	5	16
8	5,5	17	5,5	17
9	5,5	18	5,5	18
10	5	19	5	19

$E_{min} \geq 0,5 \text{ lx}$