ONTEC S20 M2X CBM B IP65
TM-S2.MXCBM060B

Click on the selected icon to download the file:

No: 1626

No: 6074/2026
Valid until:
15.04.2031

No: 88-144520
Valid until:
28.02.2027

No: 1626

No:
2291559.01.UAE
Valid until:
28.10.2026


No: 1626

No: DIT.V2.03


No: V3.1



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting, evacuation route direction**
Family	**ONTEC S20**
Colour	**black**
Colour - RAL	**RAL9005**
Version	**CBM - Central addressable modulation battery**
Operating mode	**CB**
Protection degree	**IP65**
Impact protection degree	**IK08**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, wall, ceiling, at an angle**
Luminous flux	**>2 cd/m²**
Luminous flux emergency	**154(L);309(H) lm**
Light source	**LED**
Maximum light power	**2.5 W**
Active power	**4.4 W**
LED lifetime	**100000(L);50000(H) h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**186-254 V**
Colour temperature	**5700 K**
Minimum temperature	**-15 °C**
Maximum temperature	**+55 °C**
Battery	**-**
Power Factor Correction	**0,76**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**227 mm x 40 mm x 120 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	3,5	8	3,5	8
3	3,5	9	3,5	9
4	4,5	11	4,5	11
5	5	12,5	5	12,5
6	5	14,5	5	14,5
7	5	16	5	16
8	5,5	17	5,5	17
9	5,5	18	5,5	18
10	5	19	5	19

Emin ≥ 0,5 lx