ONTEC S20 M1X 60/180 M/NM DALI B
TM-S2.MXDAX060B


Click on the selected icon to download the file:

No: 1626 | No: 6074/2026 Valid until: 15.04.2031 | No: 88-129369 | No: B_BK_60112_0426_2024 Valid until: 24.01.2030 | No: 1626 | No: 2291559.02.UAE Valid until: 05.11.2026 | No: 4882 | No: 1626


No: DIT.V2.03 | No: V3.1



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**anti-panic lighting, evacuation route direction**
Family	**ONTEC S20**
Colour	**black**
Colour - RAL	**RAL9005**
Colour structure	**smooth, gloss**
Version	**DALI**
Operating mode	**M/NM**
Duration time	**1/3 h**
Protection degree	**IP65**
Impact protection degree	**IK08**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, wall, ceiling, at an angle**
Adapted to use a pictogram	**yes**
Pictogram included	**yes**
Pictogram dimensions	**100x100 mm**
Pictogram type	**foil**
Graphic number	**K5**
Luminous flux	**>2 cd/m²**
Visibility	**20 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Light source	**LED**
Maximum light power	**3 W**
Active power	**3.8 W**
LED lifetime	**50000(1h);100000(3h) h**
Minimum temperature	**+ 0 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**227 mm x 40 mm x 120 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
*60				
2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20
*180				
2,5	3	7	3	7
3	3,5	8	3,5	8
4	4	9,5	4	9,5
5	4	11	4	11
6	3,5	12,5	3,5	12,5
7	3,5	13,5	3,5	13,5
8	3,5	14	3,5	14
9	3	14,5	3	14,5
10	2	15	2	15
Emin ≥ 0,5 lx				