

ONTEC S20 M1X 60/180 M/NM DALI W TM-S2.MXDAX060W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-129369




No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 4882



No: 1625



No: V2



No: V3.0



Producer **TM TECHNOLOGIE**

Category **emergency luminaires**

Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S20**

Colour/Colour - RAL **white , RAL9003**

Colour structure **smooth, gloss**

Version **DALI**

Operating mode **M/NM**

Duration time **1/3 h**

Protection degree **IP65**

Impact protection degree **IK08**

Appliance classes **II**

Material **plastic**

Installation method* **surface, flush-mounted, suspended, wall, ceiling, at an angle**

Adapted to use a pictogram **yes**

Pictogram included **yes**

Pictogram dimensions **100x100 mm**

Pictogram type **foil**

Graphic number **K5**

Luminous flux **>2 cd/m²**

Visibility **20 m**

Colour temperature **5700 K**

Nominal voltage AC **210-250 V**

Light source **LED**

Maximum light power **3 W**

LED lifetime **50000(1h);100000(3h) h**

Minimum temperature **+ 0 °C**

Maximum temperature **+40 °C**





Battery **LiFePO4/C (LN) 3.2V 1.5-1.6Ah**

DALI type **A**

Warranty (body, electronics, light source) **60 months**

Net dimensions **L x W x H [±2 mm]** **227 mm x 40 mm x 120 mm**





*60				
2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20
*180				
2,5	3	7	3	7
3	3,5	8	3,5	8
4	4	9,5	4	9,5
5	4	11	4	11
6	3,5	12,5	3,5	12,5
7	3,5	13,5	3,5	13,5
8	3,5	14	3,5	14
9	3	14,5	3	14,5
10	2	15	2	15
E _{min} ≥ 0,5 lx				